



# HP Latex 365 Printer

Maximize your versatility with this full-feature, 1.63-m (64-in) HP Latex printer



*Water-based HP Latex Technology is unique, delivering a combination of true application versatility, high image quality and high productivity, and a sustainable approach that's better for your operators, your business, and the environment.<sup>1</sup>*

## Expand your applications—beat client expectations

- Print on traditional signage substrates and beyond—up to 1.63 m (64 in)—print textiles with the ink collector<sup>2</sup>
- Reach new indoor spaces that solvent can't, like healthcare—water-based HP Latex Ink prints are odorless
- Enjoy efficient, automated double-sided banner printing
- Produce sharp, consistent, repeatable image quality with high-efficiency curing, 6 colors, and 1200 dpi

## Same day delivery—for highly demanding turnarounds

- High quality at high speeds—31 m<sup>2</sup> (334 ft<sup>2</sup>)/hr high-speed outdoor quality with HP OMAS, HP Latex Optimizer<sup>3</sup>
- Reach production speeds and avoid wait time—prints come out completely dry and ready to finish and deliver
- Gain productivity—reduce time between jobs with continuous printing
- You can minimize damage risk—scratch resistance is comparable to hard-solvent inks on SAV and PVC banner<sup>4</sup>

## Keep your running costs low—boost your capacity

- Increase production time and reduce time monitoring the printer—automatic, reliable, low-maintenance printing
- Save time—HP Custom Substrate Profiling and i1 embedded spectrophotometer make ICC profiling automatic<sup>5</sup>
- Maintain high image quality over the life of the printer with user-replaceable HP Thermal Inkjet printheads
- Monitor your printer remotely with the free HP Latex Mobile app<sup>6</sup>

For more information, please visit [hp.com/go/Latex365](http://hp.com/go/Latex365)

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at [hp.com/communities/LKC](http://hp.com/communities/LKC)

<sup>1</sup> Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation.

<sup>2</sup> Performance may vary depending on media—for more information, see [hp.com/go/mediasolutionslocator](http://hp.com/go/mediasolutionslocator). For best results, use textiles that do not stretch. The ink collector is required for porous textiles.

<sup>3</sup> Banner-quality prints in outdoor (4-pass 4-color) mode.

<sup>4</sup> Estimates by HP Image Permanence Lab on a range of media. Scratch-resistance comparison based on testing HP Latex Inks and representative hard-solvent inks. Outdoor display permanence tested according to SAE J2527 using HP Latex Inks on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminate. Results may vary based on specific media performance.

<sup>5</sup> ICC profiling with the spectrophotometer does not support uncoated textiles and backlits.

<sup>6</sup> HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to be connected to the Internet.

# HP Latex 365 Printer (1.63 m / 64 in)

## End-to-end sustainability—a better approach

HP Latex Technology delivers all the certifications that matter to your operators, your business, and the environment.<sup>7</sup>



Eco Mark Certification  
Number 14142007<sup>9</sup>

Using water-based inks eliminates exposure to inks with hazard warning labels and high solvent concentrations, and simplifies ventilation, storage, and transportation requirements.

HP Latex Inks enable more differentiation—odorless prints go where solvent can't.



UL GREENGUARD GOLD<sup>10</sup>

HP is designing end-to-end sustainability into large-format printing. The HP Latex 365 Printer is EPEAT Bronze registered—a designation for reduced environmental impact.<sup>11</sup>



<sup>7</sup> Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation.

<sup>8</sup> Applicable to HP Latex Inks. UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see [ul.com/EL](http://ul.com/EL)).

<sup>9</sup> HP 831 Latex Ink Cartridges, certification number 14142007, certified by the Eco Mark Office of Japan Environment Association.

<sup>10</sup> Applicable to HP Latex Inks. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit [ul.com/gg](http://ul.com/gg) or [greenguard.org](http://greenguard.org).

<sup>11</sup> EPEAT registered where applicable/supported. See [epeat.net](http://epeat.net) for registration status by country.

<sup>12</sup> Scratch-resistance comparison based on testing third-generation HP Latex Inks and representative hard-solvent inks. Estimates by HP Image Permanence Lab on a range of media.

<sup>13</sup> HP image permanence estimates by HP Image Permanence Lab. Outdoor display permanence tested according to SAE J2527 on a range of media, including HP media; in a vertical display orientation in simulated normal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminates, GBC clear gloss 1.7 mil hot laminate, or Neschen Solvoprint Performance Clear 80 laminate. Results may vary based on specific media performance.

<sup>14</sup> For best results use media options intended for double-sided printing.

<sup>15</sup> ICC profiling with the spectrophotometer does not support uncoated textiles and backlits.

<sup>16</sup> The color variation inside a printed job has been measured at 10-pass mode on vinyl media within this limit: maximum color difference (95% of colors) <= 2 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.

<sup>17</sup> Performance may vary depending on media—for more information, see [hp.com/go/mediasolutionslocator](http://hp.com/go/mediasolutionslocator). For best results, use textiles that do not stretch. The ink collector is required for porous textiles.

## HP Latex Optimizer

- Achieve high image quality at high productivity
- Interacts with HP Latex Inks to rapidly immobilize pigments on the surface of the print

## HP Latex Inks

- Scratch resistance comparable to hard-solvent inks on SAV and PVC banner—you can consider unlaminated use for short-term signage<sup>12</sup>
- Outdoor durability up to 5 years laminated, 3 years unlaminated<sup>13</sup>

## HP Latex printheads

- See fine details and smooth transitions with HP 831 Latex Printheads providing 1200 dpi native resolution
- Keep day-one image quality by replacing the printheads yourself in a few minutes, without a service call

## High-efficiency curing

- Prints are completely cured and dry inside the printer, and ready for immediate finishing and delivery



## Easy maintenance and operation

- Accessible print zone with large window and lights
- Enjoy low-maintenance printing with automatic drop detection and nozzle replacement

## HP Optical Media Advance Sensor (OMAS)

- Precise and accurate motion control of media advance between print swaths
- Controls registration automatically including double-sided prints with automated registration across sides<sup>14</sup>

HP Latex 365 Printer



- ### HP Custom Substrate Profiling
- Simplified color management, directly from the front panel, 8-inch touchscreen
  - Pre-installed generic and HP substrate profile library
  - Create custom ICC profiles with the i1 embedded spectrophotometer<sup>15</sup>

## Spectrophotometer

- Color consistency for balanced production
- i1 embedded spectrophotometer enables automatic calibration<sup>15</sup>
- Delivers consistent colors to <= 2 dE2000<sup>16</sup>
- Color emulation workflow

## Ink collector

- Expand into textile signage, no need to trim off margins
- Print on a wide variety of textiles—including porous textiles—with the ink collector<sup>17</sup>

NEW

## Easy, remote online operator training

- Online self-help learning tools—from the basics on how to start operating the printer to tips such as how to grow your business with new applications
- Visit: [hp.com/communities/HPLatex300](http://hp.com/communities/HPLatex300)

NEW

## HP Quick Solutions App

- Perform actions to optimize image quality
- Direct access from the front panel

HP Latex Technology



## Technical specifications

<b>Printing</b>	Printing modes	91 m <sup>2</sup> /hr (980 ft <sup>2</sup> /hr) - Max Speed (1 pass) 31 m <sup>2</sup> /hr (334 ft <sup>2</sup> /hr) - Outdoor High Speed (4 pass) 23 m <sup>2</sup> /hr (248 ft <sup>2</sup> /hr) - Outdoor Plus (6 pass) 17 m <sup>2</sup> /hr (183 ft <sup>2</sup> /hr) - Indoor Quality (8 pass) 14 m <sup>2</sup> /hr (151 ft <sup>2</sup> /hr) - Indoor High Quality (10 pass) 6 m <sup>2</sup> /hr (65 ft <sup>2</sup> /hr) - Backlits, Textiles, and Canvas (16 pass) 5 m <sup>2</sup> /hr (54 ft <sup>2</sup> /hr) - High Saturation Textiles (20 pass)	
	Print resolution	Up to 1200 x 1200 dpi	
	Margins	5 x 5 x 0 x 0 mm (0.2 x 0.2 x 0 x 0 in) (without edge holders)	
	Ink types	HP Latex Inks	
	Ink cartridges	Black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer	
	Cartridge size	775 ml	
	Printheads	6 (2 cyan/black, 2 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer)	
	Color consistency <sup>18</sup>	Average <= 1 dE2000, 95% of colors <= 2 dE2000	
	<b>Media</b>	Handling	Roll feed; take-up reel; automatic cutter (for vinyl, paper-based media, backlit polyester film)
		Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall-coverings, canvas, synthetics, mesh, textiles
Roll size		254 to 1625-mm (10 to 64-in) rolls (580 to 1625-mm (23 to 64-in) rolls with full support)	
Roll weight		42 kg (92.6 lb)	
Roll diameter		250 mm (9.8 in)	
Thickness	Up to 0.5 mm (19.7 mil)		
<b>Applications</b>	Banners, Displays, Double-sided banners, Exhibition and event graphics, Exterior signage, Indoor posters, Interior decoration, Light boxes – film, Light boxes – paper, Murals, POP/POS, Posters, Textile, Traffic signage, Vehicle graphics		
<b>Connectivity</b>	Interfaces	Gigabit Ethernet (1000Base-T) (standard)	
<b>Dimensions (w x d x h)</b>	Printer	2561 x 840 x 1380 mm (101 x 33 x 54 in)	
	Shipping	2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in)	
	Operating area	2761 x 1840 mm (109 x 72 in)	
<b>Weight</b>	Printer	216 kg (476 lb)	
	Shipping	303.5 kg (671.5 lb)	
<b>What's in the box</b>	HP Latex 365 Printer, printheads, maintenance cartridge, ink collector, output platen protector, printer stand, spindle, take-up reel, variable front tension kit, loading accessory, user maintenance kit, edge holders, quick reference guide, setup poster, documentation software, power cords		
<b>Environmental ranges</b>	Operating temperature	15 to 30°C (59 to 86°F)	
	Operating humidity	20 to 80% RH (non-condensing)	
<b>Acoustic</b>	Sound pressure	55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep)	
	Sound power	7.4 B(A) (printing); 5.7 B(A) (ready); < 3.5 B(A) (sleep)	
<b>Power</b>	Consumption	4.6 kW (printing); 85 watts (ready); < 2.5 watts (sleep)	
	Requirements	Input voltage (auto ranging) 200 to 240 VAC (-10% +10%) two wires and PE; 50/60 Hz (+/- 3 Hz); two power cords; 16 A max per power cord	
<b>Certification</b>	Safety	IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New Zealand (RCM)	
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI)	
	Environmental	ENERGY STAR, WEEE, RoHS (EU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT Bronze, OSHA, CE marking compliant	
<b>Warranty</b>	One-year limited hardware warranty		



## Ordering information

<b>Product</b>	V8L39A	HP Latex 365 Printer	
<b>Accessories</b>	FOM56A	HP Latex 64-in Printer 2-in Spindle	
	FOM58A	HP Latex 64-in Printer 3-in Spindle	
	FOM59A	HP Latex 300/500 User Maintenance Kit	
	T7U74A	HP Latex 300/500 Ink Collector	
<b>Original HP printheads</b>	CZ677A	HP 831 Cyan/Black Latex Printhead	
	CZ678A	HP 831 Yellow/Magenta Latex Printhead	
	CZ679A	HP 831 Light Magenta/Light Cyan Latex Printhead	
	CZ680A	HP 831 Latex Optimizer Printhead	
<b>Original HP ink cartridges and maintenance supplies</b>	CZ688A	HP 831B 775-ml Black Latex Ink Cartridge	
	CZ689A	HP 831B 775-ml Cyan Latex Ink Cartridge	
	CZ690A	HP 831B 775-ml Magenta Latex Ink Cartridge	
	CZ691A	HP 831B 775-ml Yellow Latex Ink Cartridge	
	CZ692A	HP 831B 775-ml Light Cyan Latex Ink Cartridge	
	CZ693A	HP 831B 775-ml Light Magenta Latex Ink Cartridge	
	CZ706A	HP 831 775-ml Latex Optimizer Ink Cartridge	
	CZ681A	HP 831 Latex Maintenance Cartridge	
	<b>Original HP large format printing materials</b>	HP printing materials are designed together with HP Latex Inks and HP Latex printers to provide optimal image quality, consistency, and reliability.	
		HP Permanent Gloss Adhesive Vinyl REACH <sup>19</sup>	
HP Backlit Polyester Film <sup>20</sup>			
HP PVC-free Durable Smooth Wall Paper REACH, <sup>19</sup> FSC <sup>®</sup> certified, <sup>21</sup> UL GREENGUARD GOLD Certified <sup>22</sup>			
	HP Premium Poster Paper <sup>20</sup> FSC <sup>®</sup> certified <sup>21</sup>		
	For the entire HP Large Format Printing Materials portfolio, please see <a href="http://HPLFMedia.com">HPLFMedia.com</a> .		
<b>Service and support</b>	U9JE3E	HP 2 year Next Business Day with Defective Media Retention HW Support	
	U9JE4E	HP 3 year Next Business Day with Defective Media Retention HW Support	
	U9JE7PE	HP 1 year Post Warranty Next Business Day with Defective Media Retention HW Support	
	U9JE8PE	HP 2 year Post Warranty Next Business Day with Defective Media Retention HW Support	

<sup>18</sup> The color variation inside a printed job has been measured to be within this limit: maximum color difference (95% of colors) <= 2 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard D5 014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.

<sup>19</sup> This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](http://HP Printing Products and Consumable Supplies).

<sup>20</sup> HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See [HPLFMedia.com/hp/ecosolutions](http://HPLFMedia.com/hp/ecosolutions) for details.

<sup>21</sup> BMG trademark license code FSC<sup>®</sup>-C115319, see [fsc.org](http://fsc.org). HP trademark license code FSC<sup>®</sup>-C017543, see [fsc.org](http://fsc.org). Not all FSC<sup>®</sup>-certified products are available in all regions.

<sup>22</sup> UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit [ul.com/gg](http://ul.com/gg) or [greenguard.org](http://greenguard.org).

