

HP Latex 375 Printer

More unattended printing—up to 1.63 m (64 in)—at lower cost of operation



Water-based HP Latex Technology is unique, delivering a combination of true application versatility, high image quality and high productivity, and a sustainable approach that's better for your operators, your business, and the environment.¹

Expand your applications—beat client expectations

- Get higher margins² printing on traditional signage substrates and beyond—even textiles³—up to 1.63 m (64 in)
- Reach new indoor spaces that solvent can't, like healthcare—water-based HP Latex Ink prints are odorless
- Enjoy efficient, automated double-sided banner printing
- Produce sharp, consistent, repeatable image quality with high-efficiency curing, 6 colors, and 1200 dpi

For more information, please visit hp.com/go/Latex375

Same day delivery with more unattended production

- High quality at high speeds—31 m² (334 ft²)/hr high-speed outdoor quality with HP OMAS, HP Latex Optimizer⁴
- Increase unattended printing with confidence—change 3-liter HP Latex Ink cartridges while the printer runs
- Reach production speeds and avoid wait time—prints come out completely dry and ready to finish and deliver
- You can minimize damage risk—scratch resistance is comparable to hard-solvent inks on SAV and PVC banner⁵

Keep running costs low with 3-liter ink cartridges

- Help reduce your cost per print with cost-effective, 3-liter HP 871 Latex Ink Cartridges²
- Reduce time—HP Custom Substrate Profiling and i1 embedded spectrophotometer make ICC profiling automatic⁶
- Maintain high image guality over the life of the printer with user-replaceable HP Thermal Inkjet printheads
- Monitor your printer remotely with the free HP Latex Mobile app⁷

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at hp.com/communities/LKC

7 HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to be connected to the Internet.

Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation.

For the IPL Latex 375 Printer using cost-effective, high-capacity HP 871 3-liter Latex Ink Cartridges compared to the HP Latex 365 Printer using HP 831 775-ml Latex Ink Cartridges. Performance may vary depending on media—for more information, see <u>hp.com/go/mediasolutionslocator</u>. For best results, use textiles that do not stretch. The ink collector is required for porous textiles
 Banner-quality prints in outdoor (4-pass 4-color) mode.

Estimates by HP image Permanence Lab on a range of media. Scratch-resistance comparison based on testing HP Latex Inks and representative hard-solvent inks. Outdoor display permanence tested according to SAE J2527 using HP Latex Inks on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Lear (Soc Sat Overlaminate. Results may vary based on specific media performance.
 ICC profiling with the spectrophotometer does not support uncoated textiles and backlits.

HP Latex 375 Printer (1.63 m / 64 in)

HP Latex Optimizer

- Achieve high image quality at high productivity
- Interacts with HP Latex Inks to rapidly immobilize pigments on the surface of the print

Latex 375 Printer

CONQUEROR

NEW

HP Quick Solutions App

• Direct access from the front panel

End-to-end sustainability—a better approach

HP Latex Technology delivers all the certifications that matter to your operators, your business, and the environment.⁸



Using water-based inks eliminates exposure to inks with hazard warning labels and high solvent concentrations, and simplifies ventilation, storage, and transportation requirements.

HP Latex Inks enable more differentiation—odorless prints go where solvent can't.



UL GREENGUARD GOLD¹⁰

HP is designing end-to-end sustainability into large-format printing. The HP Latex 560 Printer is EPEAT Bronze registered—a designation for reduced environmental impact.¹¹



HP Latex Inks

- Scratch resistance comparable to hard-solvent inks on SAV and PVC banner—you can consider unlaminated use for short-term signage¹²
- Outdoor durability up to 5 years laminated, 3 years unlaminated¹³

HP Latex printheads

High-efficiency curing

delivery

- See fine details and smooth transitions with HP 831 Latex Printheads providing 1200 dpi native resolution
- Keep day-one image quality by replacing the
- printheads yourself in a few minutes, without a service call



• Prints are completely cured and dry inside the

printer, and ready for immediate finishing and

Easy maintenance and operation

- Accessible print zone with large window and lights
- Enjoy low-maintenance printing with automatic
- drop detection and nozzle replacement

HP Optical Media Advance Sensor (OMAS)

- Precise and accurate motion control of media advance between print swaths
- Controls registration automatically including double-sided prints with automated registration across sides¹⁴

⁸ Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation.

- 2013 and analysis on published in 2013 published in 2013 multiple and a second method in 2013 and analysis on published in 2013 multiple and in the theology of the chology of the cholog
- greenguard.org. EPEAT registered where applicable/supported. See <u>epeat.net</u> for registration status by country.
- ¹⁹ Scratch-resistance comparison based on testing third-generation registration status by County.
 ¹⁹ HP image Permanence Lab on a range of media.
 ¹⁹ HP image Permanence Lab on a range of media.
 ¹⁹ HP image Permanence estimates by HP Image Permanence Lab. Outdoor display permanence tested according to SAE J2527 on a range of
 media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates,
 including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using
 HP Clear Gloss Cast Overlaminate, GBC clear gloss 1.7 mil hot laminate, or Neschen Solvoprint Performance Clear 80 laminate. Results may vary based
 on specific media performance.
 ¹⁴ For hest results use media notions intended for double-sided nrinting.
- For best results use media options intended for double-sided printing.

- For dest results use meala options intended for double-sided printing.
 ICC profiling with the spectrophotometer does not support uncoated textiles and backlits.
 The color variation inside a printed job has been measured at 10-pass mode on vinyl media within this limit: maximum color difference (95% of colors)
 <= 2 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant DSO, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.
 Performance may vary depending on media—for more information, see <u>hp.com/go/mediasolutionslocator</u>. For best results, use textiles that do not stretch. The ink collector is required for porous textiles.



HP Latex Technology

3-liter high-capacity HP ink cartridges

• Enjoy more unattended printing Reduce expense with cost-effective 3-liter HP Latex ink cartridges

HP Custom Substrate Profiling

- Simplified color management, directly from the front panel, 8-inch touchscreen
- Pre-installed generic and HP substrate online profile library
- Create custom ICC profiles with the i1embedded spectrophotometer¹⁵



Spectrophotometer

- Color consistency for balanced production
- i1 embedded spectrophotomer enables automatic calibration15
- Delivers consistent colors to <= 2 dE2000¹⁶
- Color emulation workflow



Ink collector

- Expand into textile signage, no need to trim off margins
- Print on a wide variety of textiles—including porous textiles—with the ink collector¹⁷



Easy, remote online operator training

• Online self-help learning tools—from the basics on how to start operating the printer to tips such as how to grow your business with new applications Visit: hp.com/communities/HPLatex300

• Perform actions to optimize image quality

Technical specifications

Printing		
	Printing modes	91 m²/hr (980 ft²/hr) - Max Speed (1 pass)
		31 m²/hr (334 ft²/hr) - Outdoor High Speed (4 pass)
		23 m²/hr (248 ft²/hr) - Outdoor Plus (6 pass)
		17 m²/hr (183 ft²/hr) - Indoor Quality (8 pass)
		14 m²/hr (151 ft²/hr) - Indoor High Quality (10 pass)
		6 m²/hr (65 ft²/hr) - Backlits, Textiles, and Canvas (16 pass)
		5 m²/hr (54 ft²/hr) - High Saturation Textiles (20 pass)
	Print resolution	Up to 1200 x 1200 dpi
	Margins	5 x 5 x 0 x 0 mm (0.2 x 0.2 x 0 x 0 in) (without edge holders)
	Ink types	HP Latex Inks
	Ink cartridges	Black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer
	Cartridge size	3 liter, 775 ml
	Printheads	6 (2 cyan/black, 2 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer)
	Color consistency ¹⁸	Average <= 1 dE2000, 95% of colors <= 2 dE2000
Media	Handling	Roll feed; take-up reel; automatic cutter (for vinyl, paper- based media, backlit polyester film)
	Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall- coverings, canvas, synthetics, mesh, textiles
	Roll size	254 to 1625-mm (10 to 64-in) rolls (580 to 1625-mm (23 to 64-in) rolls with full support)
	Roll weight	42 kg (92.6 lb)
	Roll diameter	250 mm (9.8 in)
	Thickness	Up to 0.5 mm (19.7 mil)
Applications	Banners, Displays, Double-sided banners, Exhibition and event graphics, Exterior signage, Indoor posters, Interior decoration, Light boxes – film, Light boxes – paper, Murals, POP/POS, Posters, Textile, Traffic signage, Vehicle graphics	
Connectivity	Interfaces (standard)	Gigabit Ethernet (1000Base-T)
		Gigabit Ethernet (1000Base-T) 2561 x 840 x 1380 mm (101 x 33 x 54 in)
Dimensions	(standard)	-
Dimensions	(standard) Printer	2561 x 840 x 1380 mm (101 x 33 x 54 in)
Dimensions (w x d x h)	(standard) Printer Shipping	2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in)
Dimensions (w x d x h)	(standard) Printer Shipping Operating area	2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in) 2761 x 1840 mm (109 x 72 in)
Dimensions (w x d x h) Weight What's in the	(standard) Printer Shipping Operating area Printer Shipping HP Latex 375 Prin output platen prot tension kit, loadii	2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in) 2761 x 1840 mm (109 x 72 in) 231.5 kg (510 lb)
Dimensions (w x d x h) Weight What's in the box Environmental	(standard) Printer Shipping Operating area Printer Shipping HP Latex 375 Prin output platen prot tension kit, loadii reference guide,	2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in) 2761 x 1840 mm (109 x 72 in) 231.5 kg (510 lb) 333.5 kg (734.5 lb) nter, printheads, maintenance cartridge, ink collector, stector, printer stand, spindle, take-up reel, variable front ng accessory, user maintenance kit, edge holders, quick
Dimensions (w x d x h) Weight What's in the box Environmental	(standard) Printer Shipping Operating area Printer Shipping HP Latex 375 Prin output platen pro- tension kit, loadii reference guide, Operating	2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in) 2761 x 1840 mm (109 x 72 in) 231.5 kg (510 lb) 333.5 kg (734.5 lb) nter, printheads, maintenance cartridge, ink collector, otector, printer stand, spindle, take-up reel, variable front ng accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords
Dimensions (w x d x h) Weight What's in the box Environmental ranges	(standard) Printer Shipping Operating area Printer Shipping HP Latex 375 Prin output platen prot tension kit, loadi reference guide, Operating temperature Operating	2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in) 2761 x 1840 mm (109 x 72 in) 231.5 kg (510 lb) 333.5 kg (734.5 lb) nter, printheads, maintenance cartridge, ink collector, otector, printer stand, spindle, take-up reel, variable front ng accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F)
Dimensions (w x d x h) Weight What's in the box Environmental ranges	(standard) Printer Shipping Operating area Printer Shipping HP Latex 375 Prin output platen prot tension kit, loadi reference guide, Operating temperature Operating humidity	2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in) 2761 x 1840 mm (109 x 72 in) 231.5 kg (510 lb) 333.5 kg (734.5 lb) nter, printheads, maintenance cartridge, ink collector, ptector, printer stand, spindle, take-up reel, variable front ng accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing)
Dimensions (w x d x h) Weight What's in the box Environmental ranges Acoustic	(standard) Printer Shipping Operating area Printer Shipping HP Latex 375 Prin output platen pro- tension kit, loadii reference guide, Operating temperature Operating humidity Sound pressure	2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in) 2761 x 1840 mm (109 x 72 in) 231.5 kg (510 lb) 333.5 kg (734.5 lb) nter, printheads, maintenance cartridge, ink collector, otector, printer stand, spindle, take-up reel, variable front ng accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep)
Dimensions (w x d x h) Weight What's in the box Environmental ranges Acoustic	(standard) Printer Shipping Operating area Printer Shipping HP Latex 375 Prin output platen pro- tension kit, loadii reference guide, Operating temperature Operating humidity Sound pressure Sound power	2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in) 2761 x 1840 mm (109 x 72 in) 231.5 kg (510 lb) 333.5 kg (734.5 lb) nter, printheads, maintenance cartridge, ink collector, totector, printer stand, spindle, take-up reel, variable front ng accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep) 7.4 B(A) (printing); 5.7 B(A) (ready); < 3.5 B(A) (sleep)
Dimensions (w x d x h) Weight What's in the box Environmental ranges Acoustic Power	(standard) Printer Shipping Operating area Printer Shipping HP Latex 375 Prin output platen prot tension kit, loadii reference guide, Operating temperature Operating humidity Sound pressure Sound power Consumption	2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in) 2761 x 1840 mm (109 x 72 in) 231.5 kg (510 lb) 333.5 kg (734.5 lb) nter, printheads, maintenance cartridge, ink collector, otector, printer stand, spindle, take-up reel, variable front ng accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep) 7.4 B(A) (printing); 85 watts (ready); < 2.5 watts (sleep) Input voltage (auto ranging) 200 to 240 VAC (-10% +10%) two wires and PE; 50/60 Hz (+/- 3 Hz); two power cords;
Dimensions (w x d x h) Weight What's in the box Environmental ranges Acoustic Power	(standard) Printer Shipping Operating area Printer Shipping HP Latex 375 Prin output platen prot tension kit, loadii reference guide, Operating temperature Operating humidity Sound pressure Sound power Consumption Requirements Safety	2561 × 840 × 1380 mm (101 × 33 × 54 in) 2795 × 760 × 1705 mm (110.1 × 30 × 67.2 in) 2761 × 1840 mm (109 × 72 in) 231.5 kg (510 lb) 333.5 kg (734.5 lb) hter, printheads, maintenance cartridge, ink collector, thector, printer stand, spindle, take-up reel, variable front ng accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep) 7.4 B(A) (printing); 5.7 B(A) (ready); < 3.5 B(A) (sleep) 4.6 kW (printing); 85 watts (ready); < 2.5 watts (sleep) Input voltage (auto ranging) 200 to 240 VAC (-10% +10%) two wires and PE; 50/60 Hz (+/- 3 Hz); two power cords; 16 A max per power cord IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New
Connectivity Dimensions (w x d x h) Weight What's in the box Environmental ranges Acoustic Power Certification	(standard) Printer Shipping Operating area Printer Shipping HP Latex 375 Prin output platen prot tension kit, loadii reference guide, Operating temperature Operating humidity Sound pressure Sound power Consumption Requirements Safety	2561 x 840 x 1380 mm (101 x 33 x 54 in) 2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in) 2761 x 1840 mm (109 x 72 in) 231.5 kg (510 lb) 333.5 kg (734.5 lb) hter, printheads, maintenance cartridge, ink collector, ptector, printer stand, spindle, take-up reel, variable front ng accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) 55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep) 7.4 B(A) (printing); 5.7 B(A) (ready); < 3.5 B(A) (sleep) 1nput voltage (auto ranging) 200 to 240 VAC (-10% +10%) two wires and PE; 50/60 Hz (+/- 3 Hz); two power cords; 16 A max per power cord IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New Zealand (RCM) Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and





© Copyright 2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

Ordering information

Product	V8N83A	HP Latex 375 Printer	
Accessories	F0M56A	HP Latex 64-in Printer 2-in Spindle	
	FOM58A	HP Latex 64-in Printer 3-in Spindle	
	FOM59A	HP Latex 300/500 User Maintenance Kit	
	T7U74A	HP Latex 300/500 Ink Collector	
Original HP printheads	CZ677A	HP 831 Cyan/Black Latex Printhead	
	CZ678A	HP 831 Yellow/Magenta Latex Printhead	
	CZ679A	HP 831 Light Magenta/Light Cyan Latex Printhead	
	CZ680A	HP 831 Latex Optimizer Printhead	
Original HP ink	G0Y79B	HP 871B 3-liter Cyan Latex Ink Cartridge	
cartridges and maintenance	G0Y80B	HP 871B 3-liter Magenta Latex Ink Cartridge	
maintenance supplies	G0Y81B	HP 871B 3-liter Yellow Latex Ink Cartridge	
	G0Y82B	HP 871B 3-liter Black Latex Ink Cartridge	
	G0Y83B	HP 871B 3-liter Light Cyan Latex Ink Cartridge	
	G0Y84B	HP 871B 3-liter Light Magenta Latex Ink Cartridge	
	G0Y85A	HP 871 3-liter Latex Optimizer Ink Cartridge	
	CZ688A	HP 831B 775-ml Black Latex Ink Cartridge	
	CZ689A	HP 831B 775-ml Cyan Latex Ink Cartridge	
	CZ690A	HP 831B 775-ml Magenta Latex Ink Cartridge	
	CZ691A	HP 831B 775-ml Yellow Latex Ink Cartridge	
	CZ692A	HP 831B 775-ml Light Cyan Latex Ink Cartridge	
	CZ693A	HP 831B 775-ml Light Magenta Latex Ink Cartridge	
	CZ706A	HP 831 775-ml Latex Optimizer Ink Cartridge	
	CZ681A	HP 831 Latex Maintenance Cartridge	
large format	HP printing materials are designed together with HP Latex Inks and HP Latex printers to provide optimal image quality, consistency, and reliability.		
materials	HP Permanent Gloss Adhesive Vinyl REACH ¹⁹		
	HP Backlit Polyester Film 🛟 20		
	HP PVC-free Durable Smooth Wall Paper REACH, ¹⁹ FSC [®] certified, ²¹ UL GREENGUARD GOLD Certified ²²		
	HP Premium Poster Paper 320 FSC® certified ²¹		
	For the entire HP Large Format Printing Materials portfolio, please see <u>HPLFMedia.com</u> .		
Service and support	U9JF1E	HP 2 year Next Business Day with Defective Media Retention HW Support	
	U9JF2E	HP 3 year Next Business Day with Defective Media Retention HW Support	
	U9JF5PE	HP 1 year Post Warranty Next Business Day with Defective Media Retention HW Support	
	U9JF6PE	HP 2 year Post Warranty Next Business Day with Defective Media Retention HW Support	

experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.

¹⁹ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.
 ²⁰ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See HPLEMedia.com/hp/ecosolutions for details.
 ²⁰ BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in allTregions.
 ²⁰ UL GREENGUARD OL Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg or greenguard.org.